

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/10/2020

Reviewed on 03/10/2020

16	<b>1</b>	- T - T		<u></u>	C 371		
101		nti	11 1	100			11 11
						- 1	

- · Product Identifier
- · Trade Name: Oil Foam Pro

• Relevant identified uses of the substance or mixture and uses advised against:

- · Product Description: Cylindrical solid stick in a water soluble tube
- · Application of the substance / the mixture: Dewatering natural gas wells
- · Details of the Supplier of the Safety Data Sheet:
- Manufacturer/Supplier: Croft Supply 19230 FM 442 RD Needville, TX 77461 979-793-2100
- · Emergency telephone number: (940) 855-0461

2 Hazard(s) Identification

· Classification of the substance or mixture:

Health hazard

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements:
- Hazard pictograms:



Signal word: Danger

• *Hazard-determining components of labeling:* Ammonium alcohol ether sulfate (Proprietary) Nonylphenol Polyethylene Ethoxylate

#### Hazard statements:

- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements:

- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/10/2020

#### Trade Name: Oil Foam Pro

P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves / eye protection / face protection.
P302+P352	If on skin: Wash with plenty of water.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P321	Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
P314	Get medical advice/attention if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

- 0 % of the mixture consists of component(s) of unknown toxicity.
- · Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
- NFPA ratings (scale 0 4)

310	Health = $3$ Fire = $1$ Reactivity = $0$
	Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH\*3FIRE1Fire1REACTIVITY0Physical Hazard = 0

· Hazard(s) not otherwise classified (HNOC): None known

### 3 Composition/Information on Ingredients

#### · Chemical characterization: Mixtures

· **Description:** Mixture of substances listed below with non-hazardous additions.

## Dangerous Components:

ents.	
Polyethylene Glycol	25-50%
Ethoxylated alcohol sulfate	25-50%
Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H336; Aquatic Acute 3, H402; Aquatic Chronic 3, H412	
Nonylphenol Polyethylene Ethoxylate	15-35%
♦ Eye Dam. 1, H318; ♦ Aquatic Chronic 2, H411; ♦ Acute Tox. 4, H302; Acute Tox. 4, H332	
Sodium Chloride	≤ 2.5%
	Polyethylene Glycol Ethoxylated alcohol sulfate Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H336; Aquatic Acute 3, H402; Aquatic Chronic 3, H412 Nonylphenol Polyethylene Ethoxylate Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H332

### • Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/10/2020

Reviewed on 03/10/2020

#### Trade Name: Oil Foam Pro

4 First-Aid Measures

- Description of first aid measures
- General information:

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

- After inhalation: In case of unconsciousness place patient stably in the side position for transportation.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

· After eye contact:

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention. If easy to do so, remove contact lenses if worn.

- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor
- *Most important symptoms and effects, both acute and delayed:* No further relevant information available. • *Indication of any immediate medical attention and special treatment needed:*

No further relevant information available.

#### 5 Fire-Fighting Measures

- Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: No further relevant information.
- Special hazards arising from the substance or mixture: No further relevant information available.
- Advice for firefighters
- · Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand and full protective gear to prevent contact with skin and eyes.

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment including fully-sealed eye goggled and dust respirator.

• Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

- Methods and material for containment and cleaning up:
- Ensure adequate ventilation.

Pick up mechanically.

Dispose of contaminated material as waste according to section 13.

- Reference to other sections:
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and Storage

- · Handling
- · Precautions for safe handling: Avoid contact with skin, eyes and clothing
- · Information about protection against explosions and fires: No special measures required.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/10/2020

#### Trade Name: Oil Foam Pro

- · Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: Store in the original container.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- · Specific end use(s): No further relevant information available.
- 8 Exposure Controls/Personal Protection
- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- · Components with occupational exposure limits:
- 25322-68-3 Polyethylene Glycol

WEEL Long-term value: 10 mg/m<sup>3</sup>

(H); MW>200

· Additional information: The lists that were valid during the creation of this SDS were used as basis.

- Exposure controls:
- Personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment: Not required.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

#### Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

• Eye protection:



Tightly sealed goggles

#### Limitation and supervision of exposure into the environment:

Keep away from drains, surface and ground waters. Avoid release into the environment.



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/10/2020

#### Trade Name: Oil Foam Pro

Reviewed on 03/10/2020

9 Physical and Chemical Prope	erties
<ul> <li>Information on basic physical and General Information</li> </ul>	chemical properties
<ul> <li>Appearance:</li> <li>Form:</li> <li>Color:</li> <li>Odor:</li> <li>Odor threshold:</li> </ul>	Solid Blue and White Soapy Not determined.
· pH-value:	Not applicable.
<ul> <li>Change in condition Melting point/Melting range: Boiling point/Boiling range:</li> </ul>	Not determined. ≥250 °C (≥482 °F)
· Flash point:	101 °C (213.8 °F)
· Flammability (solid, gaseous):	Not determined.
· Ignition temperature:	≥305 °C (≥581 °F)
• Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
• Danger of explosion:	Product does not present an explosion hazard.
<ul> <li>Explosion limits: Lower: Upper:</li> </ul>	Not determined. Not determined.
· Vapor pressure @ 20 °C (68 °F):	>0 hPa
<ul> <li>Density @ 20 °C (68 °F):</li> <li>Relative density:</li> <li>Vapor density:</li> <li>Evaporation rate:</li> </ul>	≥1.1469-≤1.1612 g/cm³ (≥9.5709-≤9.6902 lbs/gal) Not determined. Not applicable. Not applicable.
<ul> <li>Solubility in / Miscibility with: Water:</li> </ul>	Insoluble.
· Partition coefficient (n-octanol/wate	<i>er):</i> Not determined.
· Viscosity: Dynamic: Kinematic:	Not applicable. Not applicable.
<ul> <li>Solvent content: VOC content:</li> </ul>	0.00 %
Solids content: • Other information:	100.0 % No further relevant information available.
10 Stability and Reactivity	

· Reactivity: No further relevant information available.

· Chemical stability: Stable under normal conditions.

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• Possibility of hazardous reactions: No dangerous reactions known.

· Conditions to avoid: No further relevant information available.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/10/2020

#### Trade Name: Oil Foam Pro

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 1 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

<ul> <li>LD/LC50 values that are relevant for classification:</li> </ul>
407007 07 0 Newslybey of Debusthyleye Etherydete

127087-87	7-0 Nonylpheno	I Polyethylene Ethoxylate
Oral	LD50	16,000 mg/kg (Rat)
Dermal	LD50	4,490 mg/kg (Rabbit) (24 hr occluded contact)
Inhalative	LC50/96 hours	3.8-6.2 mg/l (Pimephales)
	LC50/48 hrs	9.3-21.4 mg/l (Water flea)
5329-14-6	Sulfamic acid	
Oral	LD50	1,321 mg/kg (Mouse)
		3,160 mg/kg (Rat)
Inhalative	LC50/96 hours	70.3 mg/l (Pimephales)
· Primary in · On the sk	ritant effect:	
Irritant to s • On the ey Strong irrit Corrosive Causes se • Additiona The prod preparation Irritant	skin and mucous re: cant with the dan effect. erious eye irritation al toxicological uct shows the ns:	ger of severe eye injury. on. <i>information:</i> following dangers according to internally approved calculation methods fo
· IARC (Inte	enic categories ernational Ager e is not listed.	: ncy for Research on Cancer):
112945-52	2-5 Amorphous	Silica 3
	onal Toxicolog le ingredients ar	
None of th	e ingredients ar	e listed.
None of th	e ingredients ar	
None of th	e ingredients ar	e listed.
12 Ecologi	cal Informati	on
Tovisitu		

- Toxicity:
- Aquatic toxicity:
- Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.
- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/10/2020

#### Trade Name: Oil Foam Pro

- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

- Harmful to aquatic organisms
- Results of PBT and vPvB assessment:
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- Other adverse effects: No further relevant information available.

13 Disposal Considerations

Fransport Information

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

· Uncleaned packaging

• *Recommendation:* Disposal must be made according to official regulations.

<ul> <li>UN-Number:</li> <li>DOT, ADR/ADN, ADN, IMDG, IATA</li> <li>UN proper shipping name:</li> <li>DOT, ADR/ADN, ADN, IMDG, IATA</li> <li>Transport hazard class(es):</li> </ul>	Non-Regulated Material Non-Regulated Material
· DOT, ADR/ADN, ADN, IMDG, IATA · Class: · Packing group:	Non-Regulated Material
DOT, ADR/ADN, IMDG, IATA Environmental hazards:	Non-Regulated Material Not applicable.
Special precautions for user:	Not applicable.
<ul> <li>Transport in bulk according to Annex II of</li> </ul>	Df
MARPOL73/78 and the IBC Code:	Not applicable.
UN "Model Regulation":	Non-Regulated Material

## 5 Regulatory Information

· Safety, health and environmental regulations/legislation specific for the substance or mixture:

• SARA (Superfund Amendments and Reauthorization):

· Section 355	(extremely hazardous substances):
None of the in	ngredients are listed.
· Section 313	(Specific toxic chemical listings):
None of the in	ngredients are listed.
· TSCA (Toxic	Substances Control Act):
25322-68-3	Polyethylene Glycol
69011-37-6	Ethoxylated alcohol sulfate
127087-87-0	Nonylphenol Polyethylene Ethoxylate
7647-14-5	Sodium Chloride

Reviewed on 03/10/2020

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/10/2020

Reviewed on 03/10/2020

Trade Name: Oil Foam Pro

	Foam Pro
25213-24-5	Polyvinyl Alcohol ( PVA, PVOH, PVAL)
112945-52-5	Amorphous Silica
9014-93-1	Dinonylphenyl polyoxyethylene
California Pr	oposition 65:
Chemicals k	nown to cause cancer:
None of the in	ngredients are listed.
Chemicals k	nown to cause reproductive toxicity for females:
None of the in	ngredients are listed.
Chemicals k	nown to cause reproductive toxicity for males:
None of the in	ngredients are listed.
Chemicals k	nown to cause developmental toxicity:
None of the in	ngredients are listed.
Carcinogenie	c categories:
EPA (Enviror	nmental Protection Agency):
None of the in	ngredients are listed.
TLV (Thresh	old Limit Value established by ACGIH):
None of the in	ngredients are listed.
NIOSH-Ca (N	lational Institute for Occupational Safety and Health):
None of the ir	ngredients are listed.
GHS label ele The product is Hazard picto	s classified and labeled according to the Globally Harmonized System (GHS).
Signal word:	
-	-
Ammonium a Nonylphenol <b>F</b> Hazard state H315 Causes	rmining components of labeling: Icohol ether sulfate (Proprietary) Polyethylene Ethoxylate ments: s skin irritation. s serious eye damage.

H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements:

- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / eye protection / face protection.
- P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- P310 Immediately call a poison center/doctor.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P314 Get medical advice/attention if you feel unwell.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/10/2020

#### Trade Name: Oil Foam Pro

P362+P364Take off contaminated clothing and wash it before reuse.P332+P313If skin irritation occurs: Get medical advice/attention.P501Dispose of contents/container in accordance with local/regional/national/international<br/>regulations.

#### National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 6 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

#### • Date of last revision/ revision number: 03/10/2020 / 2

• Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106